## **Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

## **Listing of claims:**

1. (currently amended) A method for processing a communication interruption between at least two communication devices comprising the steps of:

based on proximity to a known prediction point that is determined based on physical phenomena, predicting, during an established communication between the communication devices, that a connection to one of the communication devices will be interrupted; and

announcing that the connection to the one communication device will be interrupted.

- 2. (original) The method of claim 1 wherein at least one of the communication device is selected from a group consisting of a wireless telephone, a cellular telephone, a landline telephone, a PDA (personal digital assistant), a computer and a mobile communication device.
- 3. (original) The method of claim 1 wherein the communication interruption is based on at least one factor selected from a group consisting of a tunnel blocking the communication, a hill obstructing the communication, an indoor feature obstructing the communication, an outdoor feature obstructing the communication, lack of communication coverage by at least one cell tower, a communication frequency not available, a hand-off between at least two cell towers not available, handoff to a cell with insufficient communication channels, traveling outside the coverage area, an area with a coverage hole, a mobile switching center (MSC) error, interference from an RF source and equipment failures.





- 4. (currently amended) The method of claim 1 wherein the communication interruption prediction is based on at least one factor selected from a group consisting of the use of historical data, geographical data, enhanced location data, topographical data and GPS (Global Positioning System Satellite).
- 5. (original) The method of claim 4 wherein the historical data is collected from at least one subscriber using the communication device along a path and analyzing the communication patterns, including interruptions, along the path.
- 6. (original) The method of claim 4 wherein the geographical data is collected by mapping areas along a path for obstructions that create communication interruptions.
- 7. (original) The method of claim 4 wherein the enhanced location data is collected by observing communication flow patterns and analyzing them for any communication interruptions.
- 8. (original) The method of claim 4 wherein the topographical data is collected by mapping areas along a path for terrain that creates communication interruptions.
- 9. (currently amended)The method of claim 4 wherein the GPS (Global Positioning System Satellite) is used to observe the communication patterns and communication obstruction features and combines both to display communication interruption.
- 10. (original) The method of claim 1 wherein the announcement also contains at least one reason for the communication interruption between the devices.
- 11. (original) The method of claim 1 further comprising the step of sending a message to the other communication device indicating the reason that the connection to the one communication device has been interrupted.

- 12. (original) The method of claim 1 further comprising the step of: reconnecting to the one communication device; and re-establishing the communication.
- 13. (original) The method of claim 12 further comprising the step of: sending at least one reconnection indication to the other communication device upon a successful reconnection to the one communication device.
- 14. (original) The method of claim 1 further comprising the step of: making at least one attempt to re-establish communication between the two communication devices.
- 15. (original) The method of claim 1 further comprising the step of: attempting to reconnect to the one communication device; and if the reconnection fails, connecting the other communication device to another medium.
- 16. (original) The method of claim 15 wherein the another medium is selected from a group consisting of voice mail, a memory location, audio, data and video.
- 17. (original) The method of claim 1 wherein at least one communication device is a wireless communication device operating in conjunction with a wireless communication network having a coverage area, the method further comprising the step of: calculating the duration of the interruption prior to the announcement.
- 18. (original) The method of claim 1 wherein at least one communication device is a wireless communication device operating in conjunction with a wireless communication network having a coverage area, the method further comprising the step of: determining the reasons for the connection interruption.
- 19. (original) The method of claim 1 wherein the reason for interruption is selected from a group consisting of the communication device has traveled outside a coverage area, due to an indoor obstruction and due to an outdoor obstruction.



- 20. (original) The method of claim 1 wherein at least one communication device is a wireless communication device operating in conjunction with a wireless communication network having a coverage area, the method further comprising the step of: connecting the other communication device to voice mail without attempting to reconnect to the wireless communication device.
- 21. (currently amended) A method for processing a telephone call interruption between at least two communication devices comprising the steps of:

based on proximity to a known prediction point that is determined based on physical phenomena, predicting, during an established call between the communication devices, that a connection to one of the communication devices will be interrupted; and

announcing that the connection to the one communication device will be interrupted.

- 22. (original) The method of claim 21 further comprising the step of: reconnecting to the one communication device; and re-establishing the telephone call.
- 23. (original) The method of claim 21 wherein at least one attempt is made to reestablish communication between the two communication devices.
- 24. (original) The method of claim 21 further comprising the step of: dialing a telephone number of the one communication device.
- 25. (currently amended) A telecommunication system for processing a communication interruption between at least two communication devices comprising:

means for predicting, based on proximity to a known prediction point that is determined based on physical phenomena, during an established communication between the communication devices, that a connection to one of the communication devices will be interrupted;

means for announcing that the connection to the one communication device will be interrupted.